

Rear Blades

bühler / farm king



Series 30 to 150

From 15 hp to 150 hp :: Scrap



Series	30		45			60		80			100		150		
Model	C8315	C8317	C60SS	C72SS	C84SS	C8801	C8800	C7080	C8080	C9080	C8100	C9100	C8150	C9150	C10150
Maximum Horsepower	30	30	45	45	45	60	60	80	80	80	100	100	150	150	150
Hitch type	Category I					Category II					Category II & III				
Moldboard - Thickness						1/4"					5/16"				
	Boxed reinforcement														
- Width	5'	6'	5'	6'	7'	7'	8'	7'	8'	9'	8'	9'	8'	9'	10'
- Height	12.5"		13"			16"		18"							
Adjustment - Angle	Manual 5-position 30° left or right		Manual 5-position 40° left or right			Manual 5-position 40° left or right Hydraulic cyl. adj. optional		Manual or hydraulic 30° left or right							
- Tilt	3 pt. hitch linkage adj.		Manual 15° blade adjustment			3 pt. hitch linkage adj.		Manual or hydraulic 13° blade adjustment							
- Offset	No										Manual or hydraulic 20° left or right				
- Sideshift	No		Up to 12" off center								No				
King pin								3"			3.5"		4"		
Cutting edge	1/4" x 3" reversible		High carbon 1/2" x 6" reversible												
Weight	165	180	257	273	289	405	440	939	969	989	1287	1352	1645	1668	1703
Dual gauge wheel kit	N/A		N/A			N/A		Optional			Optional		Optional		
Skid shoes	N/A		N/A			N/A		Optional			Optional		Optional		
Racket jack	N/A		N/A			N/A		Optional			Optional		Optional		

ape up your tractor's full potential

More weight :: more strength

Buhler Farm King has been building a wide variety of rear blades for several decades. These blades are built using more steel, which adds strength, longevity and durability to each blade. Available in five series suitable for tractors ranging from 15 hp to 150 hp, Buhler Farm King rear blades are capable of tackling tough scraping projects.



Tough and precise

These rear blades have been precisely built, with particular attention to the pivot point. The tight tolerances minimize metal-on-metal wear and allows for accurate adjustments and a longer blade life.

Buhler Farm King rear blades feature a reversible and replaceable cutting edge. Most of the wear experienced during scraping is sustained by this part of the blade. When the cutting edge shows signs of excessive wear, the edge can be inverted or replaced simply by removing the bolts.

A dual gauge wheel kit and skid shoes are available on Series 80, 100 and 150 for precision grading.

Buhler Farm King rear blades are quick hitch compatible and the parking stand is standard equipment.

[1-2] Series 30 (to 30 hp) is available in 5' and 6' widths with a 30° left or right angle.

Series 45 (to 45 hp) is available in 5', 6' or 7' widths with a 40° left or right angle, offset and a 15° vertical tilt. Both feature a 5-position angle adjustment.

[3] Series 60 (to 60 hp) is available in 7' and 8' widths with a 40° left or right angle adjustment with a mechanical linkage. Hydraulic adjustment is optional.

[4] Series 80 (to 80 hp) comes in 7', 8' and 9' widths. Angle adjustment, offset and tilt can be fitted with either hydraulic cylinders or mechanical linkage.


[5] Series 100 (to 100 hp) comes in 8' and 9' widths.

Series 150 (to 150 hp) is available in 8', 9' and 10' widths. Angle adjustment, offset and tilt can be fitted with either hydraulic cylinders or mechanical linkage.





Buhler Manufacturing maintains technical staff and facilities focused on agriculture and compact equipment, including discs, box scrapers, blades and mowers. Products have undergone extensive research, field endurance and lab testing. This attention to detail ensures that product you buy from Buhler Manufacturing will be durable and reliable for years to come.



bühler / farm king

301 Mountain Street South

Morden :: Manitoba Canada R6M 1X7

Ph.: 204.822.4467 :: Fax: 204.822.6348

Toll Free: 888.524.1004

E-mail: info@buhler.com

www.buhler.com

TSX:BUI

Equipment shown is subject to change without notice at any time. ©2006 Buhler Farm King. Printed in Canada.
Ref: 082006-3000-PG